



feel the sound.....



Wave Audio Co. is a specialized designer and manufacturer of high Quality professional audio amplifiers. Our motto is to provide amplifiers, which can reproduce audio signal, as originally produced, with very clear tonal quality. The company has skilled and experienced personnel and each product is manufactured with exceptional care to offer superior sound quality to exceed the customer expectations. The parts and components are selected with utmost care and manufactured in the state of the art facility to ensure precision and reliability.

Wave Audio Co., Noida - 201301 (India)

USB 400



SPECIFICATIONS

Power Output : 40W RMS (60W max)

Input Channels : 3 MIC, 2 AUX

Digital Player : Mp3 Player with USB,
SD, MMC Card Reader,
FM and Bluetooth

Tone Control : Bass ± 10 dB at 100 Hz
Mid ± 10 dB at 1 KHz
Treble ± 10 dB at 10 KHz

Output : 200mV Pre out

Speaker Output : 4 Ω , 8 Ω , 70V, 100V

Frequency Response : 50 Hz - 15.7 KHz

S/N Ratio : 65 dB

Power Supply : AC 230V/50Hz , DC 12V

Dimensions : W425 x H100 x D300mm

Weight : 6.8 Kgs

USB 600



SPECIFICATIONS

Power Output : 60W RMS (80W max)
Input Channels : 3 MIC, 2 AUX
Digital Player : Mp3 Player with USB,
SD, MMC Card Reader,
FM Tuner and Bluetooth

Tone Control : Bass ± 10 dB at 100 Hz
Mid ± 10 dB at 1 KHz
Treble ± 10 dB at 10 KHz
Output : 200mV Pre out
Speaker Output : 4 Ω , 8 Ω , 70V, 100V

Frequency Response : 50 Hz - 15.7 KHz
S/N Ratio : 65 dB
Power Supply : AC 230V/50Hz, DC 12 V
Dimensions : W425 x H100 x D300mm
Weight : 7.6 Kgs

USB 800



SPECIFICATIONS

Power Output : 80W RMS (105W max)

Input Channels : 5 MIC, 3 AUX

Digital Player : Mp3 Player with USB,
SD, MMC Card Reader,
FM Tuner and Bluetooth

Tone Control : Bass ± 10 dB at 100 Hz

Mid ± 10 dB at 1 KHz

Treble ± 10 dB at 10 KHz

Output : 1V Line out

Speaker Output : 4 Ω , 8 Ω , 70V, 100V

Frequency Response : 50 Hz -15 KHz

S/N Ratio : 62 dB

Power Supply : AC 230V/50Hz , DC 12V

Dimensions : W410 x H140 x D320mm

Weight : 8.1 Kgs

USB 1100



SPECIFICATIONS

Power Output : 110W RMS (150W max)

Input Channels : 5 MIC, 3 AUX , 1 Line in

Digital Player : Mp3 Player with USB,
SD, MMC Card Reader,
FM Tuner and Bluetooth

Tone Control : Bass ± 10 dB at 100 Hz

Mid ± 10 dB at 1 KHz

Treble ± 10 dB at 10 KHz

Output : 1V Line out

Speaker Output : 4 Ω , 8 Ω , 70V, 100V

Frequency Response : 50 Hz -15 KHz

S/N Ratio : 62 dB

Power Supply : AC 230V/50Hz , DC 24V

Dimensions : W410 x H140 x D320mm

Weight : 9.5 Kgs

USB 1200



SPECIFICATIONS

Power Output : 120W RMS (150W max)
Input Channels : 5 MIC, 3 AUX, 1 Line in
Digital Player : Mp3 Player with USB,
 SD, MMC Card Reader,
 FM Tuner and Bluetooth

Tone Control : Bass ± 10 dB at 100 Hz
 Mid ± 10 dB at 1 KHz
 Treble ± 10 dB at 10 KHz
Output : 1V Line out
Speaker Output : 4 Ω , 8 Ω , 70V, 100V

Frequency Response : 50 Hz - 15 KHz
S/N Ratio : 62 dB
Power Supply : AC 230V/50Hz , DC 12V
Dimensions : W410 x H140 x D320mm
Weight : 9.5 Kgs

USB 1600



SPECIFICATIONS

Power Output : 160W RMS (225W max)

Input Channels : 5 MIC, 3 AUX, 1 Line in

Digital Player : Mp3 Player with USB,
SD, MMC Card Reader,
FM Tuner and Bluetooth

Tone Control : Bass ± 10 dB at 100 Hz

Mid ± 10 dB at 1 KHz

Treble ± 10 dB at 10 KHz

Output : 1V Line out

Speaker Output : $4\Omega, 8\Omega, 70V, 100V$

Frequency Response : 50 Hz - 15 KHz

S/N Ratio : 62 dB

Power Supply : AC 230V/50Hz , DC 24V

Dimensions : W410 x H140 x D320mm

Weight : 14 Kgs

USB 2500



SPECIFICATIONS

Power Output	: 250W RMS (350W max)	Tone Control	: Bass ± 10 dB at 100 Hz Mid ± 10 dB at 1 KHz Treble ± 10 dB at 10 KHz	Frequency Response	: 50 Hz - 15.7 KHz
Input Channels	: 6 MIC, 3 AUX, 1 Line in			S/N Ratio	: 62 dB
Digital Player	: Mp3 Player with USB, SD, MMC Card Reader, FM Tuner and Bluetooth	Output	: 200mV Pre out 1V Line out	Power Supply	: AC 230V/50Hz, DC 24V
		Speaker Output	: 4 Ω , 8 Ω , 70V, 100V	Dimensions	: W505 x H155 x D340mm
				Weight	: 17 Kgs

2500 AW

PROWAVE®
AMPLIFIERS



SPECIFICATIONS

Power Output : 250W RMS (350W max)

Input Channels : 6 MIC, 3 AUX, 1 Line in

Tone Control : Bass ± 10 dB at 100 Hz
Mid ± 10 dB at 1 KHz
Treble ± 10 dB at 10 KHz

Output : 200mV Pre out
1V Line out

Speaker Output : 4 Ω , 8 Ω , 70V, 100V

Frequency Response : 50 Hz - 15 KHz

S/N Ratio : 62 dB

Power Supply : AC 230V/50Hz , DC 24V

Dimensions : W505 x H155 x D340mm

Weight : 17 Kgs

USB 3000



SPECIFICATIONS

Power Output : 300W RMS (400W max)

Input Channels : 6 MIC, 3 AUX, 1 Line in

Digital Player : Mp3 Player with USB,
SD, MMC Card Reader,
FM Tuner and Bluetooth

Tone Control : Bass ± 10 dB at 100 Hz

Mid ± 10 dB at 1 KHz

Treble ± 10 dB at 10 KHz

Output : 200mV Pre out

1V Line out

Speaker Output : 4 Ω , 8 Ω , 70V, 100V

Frequency Response : 50 Hz - 15 KHz

S/N Ratio : 65 dB

Power Supply : AC 230V/50Hz, DC 24V

Dimensions : W505 x H155 x D340mm

Weight : 18 Kgs

USB 3000 EX



SPECIFICATIONS

Power Output : 300W RMS (400W max)

Input Channels : 6 MIC, 3 AUX, 1 Line in

Digital Player : Mp3 Player with USB, SD, MMC Card Reader, FM Tuner and Bluetooth

Echo : MIC 5 & MIC 6 with Repeat & Delay Control

Tone Control : Bass ± 10 dB at 100 Hz

Mid ± 10 dB at 1 KHz

Treble ± 10 dB at 10 KHz

Output : 200mV Pre out
1V Line out

Speaker Output : 4 Ω , 8 Ω , 70V, 100V

Frequency Response : 50 Hz - 15 KHz

S/N Ratio : 65 dB

Power Supply : AC 230V/50Hz, DC 24V

Dimensions : W505 x H155 x D340mm

Weight : 18.2 Kgs

USB 3500



SPECIFICATIONS

Power Output : 350W RMS (480W max)

Input Channels : 6 MIC, 3 AUX, 1 Line in

Digital Player : Mp3 Player with USB,
SD, MMC Card Reader,
FM Tuner and Bluetooth

Tone Control : Bass ± 10 dB at 100 Hz
Mid ± 10 dB at 1 KHz
Treble ± 10 dB at 10 KHz

Output : 200mV Pre out
1V Line out

Speaker Output : 4 Ω , 8 Ω , 70V, 100V

Frequency Response : 50 Hz - 15 KHz

S/N Ratio : 62 dB

Power Supply : AC 230V/50Hz , DC 24V

Dimensions : W505 x H155 x D340mm

Weight : 18.6 Kgs

3500 AW

PROWAVE®
AMPLIFIERS



SPECIFICATIONS

Power Output : 350W RMS (480W max)

Input Channels : 6 MIC, 2 AUX, 1 Line in

Tone Control : Bass ± 10 dB at 100 Hz
Mid ± 10 dB at 1 KHz
Treble ± 10 dB at 10 KHz

Output : 200mV Pre out
1V Line out

Speaker Output : 4 Ω , 8 Ω , 70V, 100V

Frequency Response : 50 Hz - 15.7 KHz

S/N Ratio : 65 dB

Power Supply : AC 230V/50Hz , DC 24V

Dimensions : W505 x H155 x D340mm

Weight : 18.5 Kgs

USB 4000



SPECIFICATIONS

Power Output : 400W RMS (500W max)

Input Channels : 6 MIC, 3 AUX , 1 Line in

Digital Player : Mp3 Player with USB,
SD, MMC Card Reader,
FM Tuner and Bluetooth

Tone Control : Bass ± 10 dB at 100 Hz
Mid ± 10 dB at 1 KHz
Treble ± 10 dB at 10 KHz

Output : 200mV Pre out
1V Line out

Speaker Output : 4 Ω , 8 Ω , 70V, 100V

Frequency Response : 50 Hz - 15 KHz

S/N Ratio : 62 dB

Power Supply : AC 230V/50Hz

Dimensions : W505 x H155 x D340mm

Weight : 20.5 Kgs

USB 5000



SPECIFICATIONS

Power Output : 500W RMS (700W max)
Input Channels : 6 MIC, 3 AUX , 1 Line in
Digital Player : Mp3 Player with USB,
SD, MMC Card Reader,
FM Tuner and Bluetooth

Tone Control : Bass ± 10 dB at 100 Hz
Mid ± 10 dB at 1 KHz
Treble ± 10 dB at 10 KHz

Output : 200mV Pre out
1V Line out

Speaker Output : 2 Ω ,4 Ω ,70V,100V

Frequency Response : 50 Hz - 15 KHz

S/N Ratio : 62 dB

Power Supply : AC 230V/50Hz

Dimensions : W495 x H155 x D420mm

Weight : 22 Kgs

AMP 5000



SPECIFICATIONS

Power Output : 500W RMS (700W max)

Input Channels : 6 MIC, 3 AUX , 1 Line in

Tone Control : Bass ± 10 dB at 100 Hz
Mid ± 10 dB at 1 KHz
Treble ± 10 dB at 10 KHz

Output : 200mV Pre out
1V Line out

Speaker Output : 2 Ω , 4 Ω , 70V, 100V

Frequency Response : 50 Hz - 15 KHz

S/N Ratio : 62 dB

Power Supply : AC 230V/50Hz

Dimensions : W495 x H155 x D420mm

Weight : 22 Kgs

USB 6000 BT



SPECIFICATIONS

Power Output : 600W RMS (850W max)
Input Channels : 1 MIC, 2 AUX, 1 Line in
Digital Player : Mp3 Player with USB,
 SD, MMC Card Reader,
 FM Tuner and Bluetooth

Tone Control : Bass ± 10 dB at 100 Hz
 Mid ± 10 dB at 1 KHz
 Treble ± 10 dB at 10 KHz
Speaker Output : 2 Ω , 4 Ω , 70V, 100V

Frequency Response : 50 Hz - 15.7 KHz
S/N Ratio : 65 dB
Power Supply : AC 230V/50Hz
Dimensions : W495 x H155 x D420mm
Weight : 23.5 Kgs

USB 6000A



SPECIFICATIONS

Power Output : 600W RMS (850W max)

Input Channels : 8 MIC, 3 AUX, 1 Line in

Digital Player : Mp3 Player with USB,
SD, MMC Card Reader,
FM and Bluetooth

Tone Control : Bass ± 10 dB at 100 Hz
Mid ± 10 dB at 1 KHz
Treble ± 10 dB at 10 KHz

Output : 200mV Pre out
1V Line out

Speaker Output : 2 Ω , 4 Ω , 70V, 100V

Frequency Response : 50 Hz - 15.7 KHz

S/N Ratio : 62 dB

Power Supply : AC 230V/50Hz

Dimensions : W495 x H155 x D420mm

Weight : 24 Kgs

6000 BW

PROWAVE®
AMPLIFIERS



SPECIFICATIONS

Power Output : 600W RMS (850W max)

Input Channels : 1 MIC, 2 AUX, 1 Line in

Tone Control : Bass ± 10 dB at 100 Hz

Mid ± 10 dB at 1 KHz

Treble ± 10 dB at 10 KHz

Speaker Output : $2\Omega, 4\Omega, 70V, 100V$

Frequency Response : 50 Hz - 15.7 KHz

S/N Ratio : 65 dB

Power Supply : AC 230V/50Hz

Dimensions : W495 x H155 x D420mm

Weight : 23.5 Kgs

USB 8000 BT



SPECIFICATIONS

Power Output : 800W RMS (1100W max)

Input Channels : 1 MIC, 2 AUX, 1 Line in

Digital Player : Mp3 Player with USB,
SD, MMC Card Reader,
FM Tuner and Bluetooth

Tone Control : Bass ± 10 dB at 100 Hz
Mid ± 10 dB at 1 KHz
Treble ± 10 dB at 10 KHz

Output : 200mV Pre out
1V Line out

Speaker Output : 2 Ω , 4 Ω , 70V, 100V

Frequency Response : 50 Hz - 15 KHz

S/N Ratio : 62 dB

Power Supply : AC 230V/50Hz

Dimensions : W410 x H140 x D320mm

Weight : 25.8 Kgs

USB 8000A



SPECIFICATIONS

Power Output	: 800W RMS (1100W max)	Tone Control	: Bass ± 10 dB at 100 Hz	Frequency Response	: 50 Hz - 15.7 KHz
Input Channels	: 8 MIC, 3 AUX, 1 Line in		Mid ± 10 dB at 1 KHz	S/N Ratio	: 65 dB
Digital Player	: MP3 Player with USB, SD, MMC Card Reader, FM Tuner and Bluetooth		Treble ± 10 dB at 10 KHz	Power Supply	: AC 230V/50Hz
		Output	: 200mV Pre out 1V Line out	Dimensions	: W425 x H100 x D300mm
		Speaker Output	: 2 Ω ,4 Ω ,70V,100V	Weight	: 26 Kgs

8000 BW



SPECIFICATIONS

Power Output : 800W RMS (1100W max)

Input Channels : 1 MIC, 2 AUX, 1 Line in

Tone Control : Bass ± 10 dB at 100 Hz
Mid ± 10 dB at 1 KHz
Treble ± 10 dB at 10 KHz

Output : 200mV Pre out
1V Line out

Speaker Output : 2 Ω , 4 Ω , 70V, 100V

Frequency Response : 50 Hz - 15 KHz

S/N Ratio : 62 dB

Power Supply : AC 230V/50Hz

Dimensions : W495 x H155 x D420mm

Weight : 25.8 Kgs

USB 10000 BT



SPECIFICATIONS

Power Output : 1000W RMS (1400W max)

Input Channels : 1 MIC, 2 AUX, 1 Line in

Digital Player : Mp3 Player with USB,
SD, MMC Card Reader,
FM and Bluetooth

Tone Control : Bass ± 10 dB at 100 Hz

Mid ± 10 dB at 1 KHz

Treble ± 10 dB at 10 KHz

Output : 200mV Pre out

1V Line out

Speaker Output : 2 Ω , 4 Ω , 70V, 100V

Frequency Response : 50 Hz - 15 KHz

S/N Ratio : 65 dB

Power Supply : AC 230V/50Hz

Dimensions : W495 x H155 x D420mm

Weight : 30.5 Kgs

USB 10000A



SPECIFICATIONS

Power Output : 1000W RMS (1400W max)

Input Channels : 8 MIC, 3 AUX , 1 Line in

Digital Player : Mp3 Player with USB,
SD, MMC Card Reader,
FM Tuner and Bluetooth

Tone Control : Bass ± 10 dB at 100 Hz

Mid ± 10 dB at 1 KHz

Treble ± 10 dB at 10 KHz

Output : 200mV Pre out

1V Line out

Speaker Output : $2\Omega, 4\Omega, 70V, 100V$

Frequency Response : 50 Hz - 15 KHz

S/N Ratio : 62 dB

Power Supply : AC 230V/50Hz

Dimensions : W495 x H155 x D420mm

Weight : 31 Kgs

10000 AW



SPECIFICATIONS

Power Output : 1000W RMS (1400W max)
Input Channels : 8 MIC, 3 AUX , 1 Line in
Tone Control : Bass ± 10 dB at 100 Hz
Mid ± 10 dB at 1 KHz
Treble ± 10 dB at 10 KHz

Output : 200mV Pre out
1V Line out
Speaker Output : 2 Ω , 4 Ω , 70V, 100V
Frequency Response : 50 Hz - 15 KHz

S/N Ratio : 62 dB
Power Supply : AC 230V/50Hz
Dimensions : W495x H155 x D420mm
Weight : 31 Kgs

10000 BW



SPECIFICATIONS

Power Output : 1000W RMS (140W max)
Input Channels : 1 MIC, 2 AUX, 1 Line in
Tone Control : Bass ± 10 dB at 100 Hz
Mid ± 10 dB at 1 KHz
Treble ± 10 dB at 10 KHz

Output : 200mV Pre out
1V Line out
Speaker Output : 2 Ω , 4 Ω , 70V, 100V
Frequency Response : 50 Hz - 15 KHz

S/N Ratio : 65 dB
Power Supply : AC 230V/50Hz
Dimensions : W495 x H155 x D420mm
Weight : 30.5 Kgs

DDX 12000



SPECIFICATIONS

Power Output : 1200W RMS (1500W max)

Input Channels : 1 Mic, 1 Aux 200 mV/1 Line in 1V

Speaker Output : 2Ω,4Ω,70V,100V

Tone Control : Bass ± 10 dB at 100 Hz

Mid ± 10 dB at 1 KHz

Treble ± 10 dB at 10 KHz

S/N Ratio : 65 dB

Frequency Response : 50 Hz - 15 KHz

Power Supply : AC 230V/50Hz

Dimensions : W495 x H155 x D420mm

Weight : 29 Kgs

DDX 16000



SPECIFICATIONS

Power Output : 1600W RMS (2000W max)

Input Channels : 1 Mic, 1 Aux 200 mV/1 Line in 1V

Speaker Output : 2 Ω , 4 Ω , 70V, 100V

Tone Control : Bass ± 10 dB at 100 Hz

Mid ± 10 dB at 1 KHz

Treble ± 10 dB at 10 KHz

S/N Ratio : 65 dB

Frequency Response : 50 Hz - 15 KHz

Power Supply : AC 230V/50Hz

Dimensions : W495 x H155 x D420mm

Weight : 32 Kgs

22000 BW



SPECIFICATIONS

Power Output : 2200W (2800W max)
Input Channels : 1 MIC, 1 AUX, 1 Line in
Speaker Output : 2 Ω , 4 Ω , 70V, 100V

Tone Control : Bass ± 10 dB at 100 Hz
Mid ± 10 dB at 1 KHz
Treble ± 10 dB at 10 KHz
S/N Ratio : 60 dB

Frequency Response : 60 Hz - 15 KHz
Power Supply : AC 230V/50Hz
Dimensions : W545 x H160 x D510mm
Weight : 39 Kgs

32000 BW

PROWAVE®
AMPLIFIERS



SPECIFICATIONS

Power Output : 3200W (4000W max)
Input Channels : 1 MIC, 1 AUX, 1 Line in
Speaker Output : 2Ω, 4Ω, 70V, 100V

Tone Control : Bass ±10 dB at 100 Hz
Mid ±10 dB at 1 KHz
Treble ±10 dB at 10 KHz
S/N Ratio : 60 dB

Frequency Response : 60 Hz - 15 KHz
Power Supply : AC 230V/50Hz
Dimensions : W545 x H160 x D510mm
Weight : 44 Kgs

USB 1500 DZ



SPECIFICATIONS

Power Output : 75+75W RMS (105W max)

Input Channels : 6 MIC, 2 AUX , 1 Stereo input

Digital Player : Mp3 Player with USB,
SD, MMC Card Reader,
FM and Bluetooth

Tone Control : Bass ± 10 dB at 100 Hz
Mid ± 10 dB at 1 KHz
Treble ± 10 dB at 10 KHz

Output : 200mV Pre out
2x1V Line out

Speaker Output : 4 Ω , 8 Ω , 70V, 100V

Frequency Response : 50 Hz - 15 KHz

S/N Ratio : 62 dB

Power Supply : AC 230V/50Hz, DC 12V

Dimensions : W505 x H155 x D340mm

Weight : 14 Kgs

USB 2000 DZ



SPECIFICATIONS

Power Output : 100+100W RMS (150W max)

Input Channels : 6 MIC, 2 AUX , 1 Stereo input

Digital Player : Mp3 Player with USB,
SD, MMC Card Reader,
FM and Bluetooth

Tone Control : Bass ± 10 dB at 100 Hz
Mid ± 10 dB at 1 KHz
Treble ± 10 dB at 10 KHz

Output : 200mV Pre out
2x1V Line out

Speaker Output : 4 Ω ,8 Ω ,70V,100V

Frequency Response : 50 Hz - 15 KHz

S/N Ratio : 62 dB

Power Supply : AC 230V/50Hz, DC 24V

Dimensions : W505 x H155 x D340mm

Weight : 15 Kgs

2000A DZ



SPECIFICATIONS

Power Output : 100+100W RMS (140W max)

Input Channels : 6 MIC, 2 AUX , 1 Stereo input

Tone Control : Bass ± 10 dB at 100 Hz
Mid ± 10 dB at 1 KHz
Treble ± 10 dB at 10 KHz

Output : 200mV Pre out
2x1V Line out

Speaker Output : 4 Ω , 8 Ω , 70V, 100V

S/N Ratio : 62 dB

Frequency Response : 50 Hz - 15 KHz

Power Supply : AC 230V/50Hz, DC 24V

Dimensions : W505 x H155 x D340mm

Weight : 15 Kgs

USB 3000 DZ



SPECIFICATIONS

Power Output : 150+150W RMS (200W max)

Input Channels : 6 MIC, 2 AUX , 1 Stereo input

Digital Player : Mp3 Player with USB,
SD, MMC Card Reader,
FM and Bluetooth

Tone Control : Bass ± 10 dB at 100 Hz
Mid ± 10 dB at 1 KHz
Treble ± 10 dB at 10 KHz

Output : 200mV Pre out
2x1V Line out

Speaker Output : 4 Ω ,8 Ω ,70V,100V

Frequency Response : 50 Hz - 15 KHz

S/N Ratio : 60 dB

Power Supply : AC 230V/50Hz, DC 24V

Dimensions : W505 x H155 x D340mm

Weight : 15 Kgs

3000A DZ



SPECIFICATIONS

Power Output : 150+150W RMS (200W max)
Input Channels : 6 MIC, 2 AUX , 1 Stereo input
Tone Control : Bass ± 10 dB at 100 Hz
Mid ± 10 dB at 1 KHz
Treble ± 10 dB at 10 KHz

Output : 200mV Pre out
2x1V Line out
Speaker Output : 4 Ω , 8 Ω , 70V, 100V
S/N Ratio : 62 dB

Frequency Response : 50 Hz - 15 KHz
Power Supply : AC 230V/50Hz, DC 24V
Dimensions : W505 x H155 x D340mm
Weight : 16 Kgs

USB 4000 DZ



SPECIFICATIONS

Power Output : 200+200W RMS (275W max)

Input Channels : 6 MIC, 2 AUX

1 Stereo input, 2 Line in

Digital Player : Mp3 Player with USB,
SD, MMC Card Reader,
FM and Bluetooth

Tone Control : Bass ± 10 dB at 100 Hz

Mid ± 10 dB at 1 KHz

Treble ± 10 dB at 10 KHz

Output : 200mV Pre out

2x1V Line out

Speaker Output : 4 Ω , 8 Ω , 70V, 100V

Frequency Response : 50 Hz - 15 KHz

S/N Ratio : 62 dB

Power Supply : AC 230V/50Hz

Dimensions : W495 x H155 x D420mm

Weight : 23.5 Kgs

4000A DZ



SPECIFICATIONS

Power Output : 200+200W RMS (280W max)
Input Channels : 6 MIC, 2 AUX
1 Stereo input, 2 Line in
Tone Control : Bass ± 10 dB at 100 Hz
Treble ± 10 dB at 10 KHz

Output : 200mV Pre out
2x1V Line out
Speaker Output : 4 Ω , 8 Ω , 70V, 100V
S/N Ratio : 62 dB

Frequency Response : 50 Hz - 15 KHz
Power Supply : AC 230V/50Hz
Dimensions : W495 x H155 x D420mm
Weight : 23 Kgs

USB 5000 DZ



SPECIFICATIONS

Power Output : 250+250W RMS (350W max)

Input Channels : 6 MIC, 2 AUX

1 Stereo input, 2 Line in

Digital Player : Mp3 Player with USB,
SD, MMC Card Reader,
FM and Bluetooth

Tone Control : Bass ± 10 dB at 100 Hz

Mid ± 10 dB at 1 KHz

Treble ± 10 dB at 10 KHz

Output : 200mV Pre out

2x1V Line out

Speaker Output : 4 Ω , 8 Ω , 70V, 100V

Frequency Response : 50 Hz - 15 KHz

S/N Ratio : 62 dB

Power Supply : AC 230V/50Hz

Dimensions : W495 x H155 x D420mm

Weight : 24.5 Kgs

5000A DZ



SPECIFICATIONS

Power Output : 250+250W RMS (350W max)
Input Channels : 6 MIC, 2 AUX
 1 Stereo input, 2 Line in
Tone Control : Bass ± 10 dB at 100 Hz
 Treble ± 10 dB at 10 KHz

Output : 200mV Pre out
 2x1V Line out
Speaker Output : 4 Ω , 8 Ω , 70V, 100V
S/N Ratio : 62 dB

Frequency Response : 50 Hz - 15 KHz
Power Supply : AC 230V/50Hz
Dimensions : W495 x H155 x D420mm
Weight : 24.5 Kgs

USB 7000 DZ



SPECIFICATIONS

Power Output : 350+350W RMS (480W max)

Input Channels : 6 MIC, 2 AUX

1 Stereo input, 2 Line in

Digital Player : Mp3 Player with USB,
SD, MMC Card Reader,
FM and Bluetooth

Tone Control : Bass ± 10 dB at 100 Hz

Mid ± 10 dB at 1 KHz

Treble ± 10 dB at 10 KHz

Output : 200mV Pre out

2x1V Line out

Speaker Output : 4 Ω , 8 Ω , 70V, 100V

Frequency Response : 50 Hz - 15 KHz

S/N Ratio : 62 dB

Power Supply : AC 230V/50Hz

Dimensions : W495 x H155 x D420mm

Weight : 28 Kgs

7000A DZ



SPECIFICATIONS

Power Output : 350+350W RMS (480W max)

Input Channels : 6 MIC, 2 AUX

1 Stereo input, 2 Line in

Tone Control : Bass ± 10 dB at 100 Hz

Treble ± 10 dB at 10 KHz

Output : 200mV Pre out
2x1V Line out

Speaker Output : 4 Ω , 8 Ω , 70V, 100V

S/N Ratio : 62 dB

Frequency Response : 50 Hz - 15 KHz

Power Supply : AC 230V/50Hz

Dimensions : W495 x H155 x D420mm

Weight : 28 Kgs

USB 10000 DZ



SPECIFICATIONS

Power Output : 500+500W RMS (700W max)

Input Channels : 6 MIC, 2 AUX

1 Stereo input, 2 Line in

Digital Player : Mp3 Player with USB,
SD, MMC Card Reader,
FM and Bluetooth

Tone Control : Bass ± 10 dB at 100 Hz

Mid ± 10 dB at 1 KHz

Treble ± 10 dB at 10 KHz

Output : 200mV Pre out

2x1V Line out

Speaker Output : 2 Ω , 4 Ω , 70V, 100V

Frequency Response : 50 Hz - 15 KHz

S/N Ratio : 62 dB

Power Supply : AC 230V/50Hz

Dimensions : W550 x H155 x D460mm

Weight : 34 Kgs

10000A DZ



SPECIFICATIONS

Power Output : 500+500W RMS (700W max)
Input Channels : 6 MIC, 2 AUX
 1 Stereo input, 2 Line in
Tone Control : Bass ± 10 dB at 100 Hz
 Treble ± 10 dB at 10 KHz

Output : 200mV Pre out
 2x1V Line out
Speaker Output : 2 Ω , 4 Ω , 70V, 100V
S/N Ratio : 62 dB

Frequency Response : 50 Hz - 15 KHz
Power Supply : AC 230V/50Hz
Dimensions : W495 x H155 x D420mm
Weight : 34 Kgs

USB 12000 DZ



SPECIFICATIONS

Power Output : 600+600W RMS (800W max)

Input Channels : 6 MIC, 2 AUX

1 Stereo input, 2 Line in

Digital Player : Mp3 Player with USB,
SD, MMC Card Reader,
FM and Bluetooth

Tone Control : Bass ± 10 dB at 100 Hz

Mid ± 10 dB at 1 KHz

Treble ± 10 dB at 10 KHz

Output : 200mV Pre out

2x1V Line out

Speaker Output : 2 Ω , 4 Ω , 70V, 100V

Frequency Response : 50 Hz - 15 KHz

S/N Ratio : 62 dB

Power Supply : AC 230V/50Hz

Dimensions : W550 x H155 x D460mm

Weight : 38 Kgs

TZ 300+300



SPECIFICATIONS

Power Output : 300+300W RMS (430W max)

Input Channels : 1 MIC, 2 AUX

1 Stereo input, 2 Line in

Tone Control : Bass ± 10 dB at 100 Hz
Treble ± 10 dB at 10 KHz

Output : 200mV Pre out
2x1V Line out

Speaker Output : 4 Ω , 8 Ω , 70V, 100V

S/N Ratio : 62 dB

Frequency Response : 50 Hz - 15 KHz

Power Supply : AC 230V/50Hz

Dimensions : W495 x H155 x D420mm

Weight : 27.5 Kgs

TZ 400+400



SPECIFICATIONS

Power Output : 400+400W RMS (550W max)
Input Channels : 1 MIC, 2 AUX
 1 Stereo input, 2 Line in
Tone Control : Bass ± 10 dB at 100 Hz
 Treble ± 10 dB at 10 KHz

Output : 200mV Pre out
 2x1V Line out
Speaker Output : 4 Ω , 8 Ω , 70V, 100V
S/N Ratio : 62 dB

Frequency Response : 50 Hz - 15 KHz
Power Supply : AC 230V/50Hz
Dimensions : W495 x H155 x D420mm
Weight : 30.8 Kgs

TZ 500+500



SPECIFICATIONS

Power Output : 500+500W RMS (700W max)

Input Channels : 1 MIC, 2 AUX

1 Stereo input, 2 Line in

Tone Control : Bass ± 10 dB at 100 Hz
Treble ± 10 dB at 10 KHz

Output : 200mV Pre out
2x1V Line out

Speaker Output : $2\Omega, 4\Omega, 70V, 100V$

S/N Ratio : 62 dB

Frequency Response : 50 Hz - 15 KHz

Power Supply : AC 230V/50Hz

Dimensions : W495 x H155 x D420mm

Weight : 30.7 Kgs

TZ 600+600



SPECIFICATIONS

Power Output : 600+600W RMS (800W max)

Input Channels : 2 AUX, 2 Line in

Tone Control : Bass ± 10 dB at 100 Hz
Mid ± 10 dB at 1 KHz
Treble ± 10 dB at 10 KHz

Output : 2x200mV Pre out
2x1V Line out

Speaker Output : 2 Ω , 4 Ω , 70V, 100V

S/N Ratio : 62 dB

Frequency Response : 50 Hz - 15 KHz

Power Supply : AC 230V/50Hz

Dimensions : W550 x H165 x D460mm

Weight : 38 Kgs

TZ 22000

PROWAVE®
AMPLIFIERS



SPECIFICATION

Power Output : 1100+1100W (1500W max)
Input Channels : 1 MIC, 2 AUX, 2 Line in
Tone Control : Bass ± 10 dB at 100 Hz
Mid ± 10 dB at 1 KHz
Treble ± 10 dB at 10 KHz

Output : 2x1V Line out
Speaker Output : 2 Ω , 4 Ω , 70V, 100V
S/N Ratio : 62 dB

Frequency Response : 50 Hz - 15 KHz
Power Supply : AC 230V/50Hz
Dimensions : W545 x H160 x D510mm
Weight : 44.5 Kgs

TZ 32000



SPECIFICATION

Power Output : 1600+1600W (2200W max)
Input Channels : 1 MIC, 2 AUX, 2 Line in
Tone Control : Bass ± 10 dB at 100 Hz
Mid ± 10 dB at 1 KHz
Treble ± 10 dB at 10 KHz

Output : 2x1V Line out
Speaker Output : $2\Omega, 4\Omega, 70V, 100V$
S/N Ratio : 62 dB

Frequency Response : 50 Hz - 15 KHz
Power Supply : AC 230V/50Hz
Dimensions : W545 x H160 x D510mm
Weight : 48.6 Kgs



Wave Audio Co.

Noida - 201301 (India)

Our Channel Partner